

TYRES

Product group	Tyres
Item number	15726566
Valid tyre size	280 / 70 R 18
LI / SI / PR	114 A8 / 114 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726566
EAN	8903094021901
Valid tyre size	280 / 70 R 18
LI / SI / PR	114 A8 / 114 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	28,40
Recommended rim size	W9
Permitted rim size	W8, W10
Maximum air pressure [bar].	2,40
Section width (mm)	282
Outer diameter of tyre [mm].	849
Stat. radius (SLR) [mm]	381
Rolling circumference [mm].	2547
Tread depth (mm)	32,0
Number of lugs	17x2
Lug width (mm)	25
Tyre capacity 75% [ltr.]	49.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
114 A8	1180	40		2,40	
114 B	1180	50		2,40	