

TYRES

Product group	Tyres	
Item number	15726568	
Valid tyre size	260 / 70 R 20	
LI / SI / PR	113 A8 / 113 B	
TL/TT	TL	
Brand	BKT	
Tread pattern	Agrimax RT 765	





Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.



Technical Informations

Mana mumahan	15720500
Item number	15726568
EAN	8903094030576
Valid tyre size	260 / 70 R 20
LI / SI / PR	113 A8 / 113 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	26,63
Recommended rim size	W8
Permitted rim size	9, W9
Maximum air pressure [bar].	2,40
Section width (mm)	258
Outer diameter of tyre [mm].	872
Stat. radius (SLR) [mm]	402
Rolling circumference [mm].	2639
Tread depth (mm)	30,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	46.5
E-Ready	No



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
113 A8	1150	40		2,40	
113 B	1150	50		2,40	