

## TYRES

Product group	Tyres
Item number	15726590
Valid tyre size	320 / 70 R 20
LI / SI / PR	123 A8 / 123 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765



## Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Low soil compaction and good self-cleaning properties.
- Mainly used both in arable farming and grassland.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

## Technical Informations

Item number	15726590
EAN	8903094021932
Valid tyre size	320 / 70 R 20
LI / SI / PR	123 A8 / 123 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	39,40
Recommended rim size	W10
Permitted rim size	W9, W11
Maximum air pressure [bar].	2,40
Section width (mm)	319
Outer diameter of tyre [mm].	982
Stat. radius (SLR) [mm]	445
Rolling circumference [mm].	2938
Tread depth (mm)	33,0
Number of lugs	17x2
Lug width (mm)	28
Tyre capacity 75% [ltr.]	78.75
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
123 A8	1550	40		2,40	
123 B	1550	50		2,40	