

## TYRES

Product group	Tyres
Item number	15726600
Valid tyre size	360 / 70 R 20
LI / SI / PR	129 A8 / 129 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765



## Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Low soil compaction and good self-cleaning properties.
- Mainly used both in arable farming and grassland.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

**Technical Informations**

<b>Item number</b>	15726600
<b>EAN</b>	8903094021949
<b>Valid tyre size</b>	360 / 70 R 20
<b>LI / SI / PR</b>	129 A8 / 129 B
<b>TL/TT</b>	TL
<b>Brand</b>	BKT
<b>Tread pattern</b>	Agrimax RT 765
<b>Antistatic</b>	No
<b>Tyre colour</b>	Black
<b>ECE regulation number</b>	ECE 106
<b>Nettogewicht [kg] (gültig)</b>	52,48
<b>Recommended rim size</b>	W11
<b>Permitted rim size</b>	W10, W12
<b>Maximum air pressure [bar].</b>	2,40
<b>Section width (mm)</b>	357
<b>Outer diameter of tyre [mm].</b>	1042
<b>Stat. radius (SLR) [mm]</b>	469
<b>Rolling circumference [mm].</b>	3122
<b>Tread depth (mm)</b>	41,0
<b>Number of lugs</b>	17x2
<b>Lug width (mm)</b>	30
<b>Tyre capacity 75% [ltr.]</b>	107.25
<b>E-Ready</b>	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
129 A8	1850	40		2,40	
129 B	1850	50		2,40	