

TYRES

| Product group | Tyres |
|-----------------|----------------|
| Item number | 15726602 |
| Valid tyre size | 380 / 70 R 20 |
| LI / SI / PR | 132 A8 / 132 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 765 |





Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.



Technical Informations

| Item number | 15726602 |
|------------------------------|----------------|
| EAN | 8903094021987 |
| Valid tyre size | 380 / 70 R 20 |
| LI / SI / PR | 132 A8 / 132 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 765 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 59,80 |
| Recommended rim size | W12 |
| Permitted rim size | W11, W13 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 380 |
| Outer diameter of tyre [mm]. | 1082 |
| Stat. radius (SLR) [mm] | 482 |
| Rolling circumference [mm]. | 3213 |
| Tread depth (mm) | 42,0 |
| Number of lugs | 17x2 |
| Lug width (mm) | 32 |
| Tyre capacity 75% [ltr.] | 123.75 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 132 A8 | 2000 | 40 | | 2,40 | |
| 132 B | 2000 | 50 | | 2,40 | |