

TYRES

Product group	Tyres
Item number	15726641
Valid tyre size	460 / 70 R 24
LI / SI / PR	159 A8 / 156 B
TL/TT	TL
Brand	BKT
Tread pattern	Agro Industrial RT 747



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Wide contact surface ensures optimum ground protection.
- Reduced rolling resistance lowers fuel consumption.
- New lug design with optimal traction.
- Sturdy carcass construction offers high load capacity reserves.
- Special rubber compound ensures long service life.

Technical Informations

Item number	15726641
EAN	8903094059270
Valid tyre size	460 / 70 R 24
Alternative size 1	17.5LR24
LI / SI / PR	159 A8 / 156 B
TL/TT	TL
Brand	BKT
Tread pattern	Agro Industrial RT 747
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	94,56
Recommended rim size	DW15L
Permitted rim size	DW14L, DW16L
Maximum air pressure [bar].	4,00
Section width (mm)	465
Outer diameter of tyre [mm].	1254
Stat. radius (SLR) [mm]	556
Rolling circumference [mm].	3840
Tread depth (mm)	39,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		4,00	
156 B	4000	50		4,00	