

TYRES

Product group	Tyres
Item number	15726644
Valid tyre size	19.5L R 24
LI / SI / PR	157 A8 / 154 B
TL/TT	TL
Brand	BKT
Tread pattern	Agro Industrial RT 747



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Wide contact surface ensures optimum ground protection.
- Reduced rolling resistance lowers fuel consumption.
- New lug design with optimal traction.
- Sturdy carcass construction offers high load capacity reserves.
- Special rubber compound ensures long service life.

Technical Informations

Item number	15726644
EAN	8903094016822
Valid tyre size	19.5L R 24
Alternative size 1	500/70R24
LI / SI / PR	157 A8 / 154 B
TL/TT	TL
Brand	BKT
Tread pattern	Agro Industrial RT 747
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	114,40
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	3,00
Section width (mm)	485
Outer diameter of tyre [mm].	1320
Stat. radius (SLR) [mm]	585
Rolling circumference [mm].	3949
Tread depth (mm)	42,0
Number of lugs	18x2
Lug width (mm)	48
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A8	4125	40		3,00	
	3750	50		3,00	