

TYRES

Product group	Tyres
Item number	15726651
Valid tyre size	480 / 70 R 24
LI / SI / PR	138 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Low soil compaction and good self-cleaning properties.
- Mainly used both in arable farming and grassland.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726651
EAN	8903094062195
Valid tyre size	480 / 70 R 24
LI / SI / PR	138 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	98,98
Recommended rim size	W15L
Permitted rim size	W14L, W16L
Maximum air pressure [bar].	1,60
Section width (mm)	479
Outer diameter of tyre [mm].	1316
Stat. radius (SLR) [mm]	580
Rolling circumference [mm].	3894
Tread depth (mm)	48,5
Number of lugs	18x2
Lug width (mm)	39
Tyre capacity 75% [ltr.]	251.25
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 D	2360	65		1,60	