

TYRES

Product group	Tyres
Item number	15726658
Valid tyre size	620 / 75 R 26
LI / SI / PR	167 A8 / 167 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
- Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf.
- Large footprint enables excellent flotation properties.
- Reinforced bead provides high load capacity.

Technical Informations

Item number	15726658
EAN	8903094050444
Valid tyre size	620 / 75 R 26
Alternative size 1	23.1R26
LI / SI / PR	167 A8 / 167 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	177,00
Recommended rim size	DW20B
Maximum air pressure [bar].	3,20
Section width (mm)	625
Tread width (mm)	560
Outer diameter of tyre [mm].	1590
Stat. radius (SLR) [mm]	730
Speed Radius Index (SRI)	750
Rolling circumference [mm].	4851
Tread depth (mm)	45,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	567.75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 A8	5450	40		3,20	
167 B	5450	50		3,20	