

TYRES

Product group	Tyres	
Item number	15726711	
Valid tyre size	380 / 70 R 28	
LI / SI / PR	127 D	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Agrimax RT 765	





Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.



Technical Informations

Item number	15726711
EAN	8903094063055
Valid tyre size	380 / 70 R 28
LI / SI / PR	127 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	73,50
Recommended rim size	W12
Permitted rim size	W11, W13
Maximum air pressure [bar].	1,60
Section width (mm)	380
Outer diameter of tyre [mm].	1293
Stat. radius (SLR) [mm]	586
Rolling circumference [mm].	3883
Tread depth (mm)	42,0
Number of lugs	20x2
Lug width (mm)	34
Tyre capacity 75% [ltr.]	161.25
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
127 D	1750	65		1,60	