

TYRES

Product group	Tyres
Item number	15726784
Valid tyre size	600 / 70 R 30
LI / SI / PR	152 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726784
EAN	8903094062256
Valid tyre size	600 / 70 R 30
LI / SI / PR	152 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	171,60
Recommended rim size	DW20B
Permitted rim size	DW18L, W18L
Maximum air pressure [bar].	1,60
Section width (mm)	591
Outer diameter of tyre [mm].	1602
Stat. radius (SLR) [mm]	711
Rolling circumference [mm].	4774
Tread depth (mm)	57,5
Number of lugs	18x2
Tyre capacity 75% [ltr.]	489
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 D	3550	65		1,60	