

## TYRES

|                 |                      |
|-----------------|----------------------|
| Product group   | Tyres                |
| Item number     | 15726788             |
| Valid tyre size | VF 600 / 70 R 30 NRO |
| LI / SI / PR    | 168 D                |
| TL/TT           | TL                   |
| Brand           | BKT                  |
| Tread pattern   | Agrimax V-Flecto     |



## Notes and features

- The BKT Agrimax V-Flecto is a VF tyre of the new generation.
- Compared with a standard tyre, the tyre achieves 40% more load capacity at the same inflation pressure or the same load capacity with 40% less inflation pressure.
- In contrast to most VF tyres, the tyre can be mounted on a standard rim (NRO=Narrow Rim Option).
- Its 10 % larger contact area compared with a standard tyre enables outstanding traction while significantly reducing soil compaction.
- The specially shaped bead (Bead Protection System) closes extremely airtight and keeps the inflation pressure constant in all conditions.
- During road journeys, the particular lug angles ensure reduced vibrations and noise levels.
- There is no need to adjust the inflation pressure for optimum performance both in the field and on the road
- The extremely strong polyester casing provides a 10 % longer service life in comparison with a standard tyre, even in difficult conditions.

## Technical Informations

|                              |                      |
|------------------------------|----------------------|
| Item number                  | 15726788             |
| EAN                          | 8903094064601        |
| Valid tyre size              | VF 600 / 70 R 30 NRO |
| LI / SI / PR                 | 168 D                |
| TL/TT                        | TL                   |
| Brand                        | BKT                  |
| Tread pattern                | Agrimax V-Flecto     |
| Antistatic                   | No                   |
| Tyre colour                  | Black                |
| ECE regulation number        | ECE 106              |
| Nettogewicht [kg] (gültig)   | 196,67               |
| Recommended rim size         | DW21B                |
| Permitted rim size           | DW20B, DW18B         |
| Maximum air pressure [bar].  | 2,00                 |
| Section width (mm)           | 603                  |
| Tread width (mm)             | 565                  |
| Outer diameter of tyre [mm]. | 1602                 |
| Stat. radius (SLR) [mm]      | 702                  |
| Rolling circumference [mm].  | 4711                 |
| Tread depth (mm)             | 58,5                 |
| Number of lugs               | 20x2                 |
| Tyre capacity 75% [ltr.]     | 448.50               |
| E-Ready                      | No                   |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 168 D | 5600               | 65           |               | 2,00                     |              |