

TYRES

Product group	Tyres
Item number	15726790
Valid tyre size	600 / 70 R 30
LI / SI / PR	161 A8 / 158 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Fortis



Bohnenkamp
Moving Professionals



Notes and features

- Super wide tyres for high performance tractors from about 200 hp.
- High load capacities paired with excellent traction, due to extended contact area and solid lugs.
- Efficient in agricultural use and increased transport performance with high ride comfort and lower rolling resistance.
- Reduction of operating costs through fuel savings and high mileage.

Technical Informations

Item number	15726790
EAN	8903094032952
Valid tyre size	600 / 70 R 30
LI / SI / PR	161 A8 / 158 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Fortis
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	181,94
Recommended rim size	DW20B
Permitted rim size	DW18L, W18L
Maximum air pressure [bar].	2,40
Section width (mm)	611
Outer diameter of tyre [mm].	1602
Stat. radius (SLR) [mm]	724
Rolling circumference [mm].	4810
Tread depth (mm)	58,0
Number of lugs	18x2
Lug width (mm)	43
Tyre capacity 75% [ltr.]	489
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 A8	4625	40		2,40	
158 D	4250	65		2,40	