

## **TYRES**

Product group	Tyres	
Item number	15726805	
Valid tyre size	IF 710 / 75 R 32 CFO	
LI / SI / PR	183 A8 / 183 B	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Agrimax Teris	



## Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.



## **Technical Informations**

Item number	15726805
EAN	8903094059249
Valid tyre size	IF 710 / 75 R 32 CFO
LI / SI / PR	183 A8 / 183 B
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax Teris
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	337,30
Recommended rim size	DW25B
Permitted rim size	DW23B
Maximum air pressure [bar].	3,20
Section width (mm)	716
Tread width (mm)	676
Outer diameter of tyre [mm].	1879
Stat. radius (SLR) [mm]	851
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5653
Tread depth (mm)	61,5
Number of lugs	19x2
Tyre capacity 75% [ltr.]	778.87
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
183 A8	8750	40		3,20	
183 B	8750	50		3,20	