

TYRES

Product group	Tyres
Item number	15726850
Valid tyre size	600 / 70 R 34
LI / SI / PR	163 A8 / 160 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Fortis



Bohnenkamp
Moving Professionals



Notes and features

- Super wide tyres for high performance tractors from about 200 hp.
- High load capacities paired with excellent traction, due to extended contact area and solid lugs.
- Efficient in agricultural use and increased transport performance with high ride comfort and lower rolling resistance.
- Reduction of operating costs through fuel savings and high mileage.

Technical Informations

Item number	15726850
EAN	8903094035649
Valid tyre size	600 / 70 R 34
LI / SI / PR	163 A8 / 160 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Fortis
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	193,92
Recommended rim size	DW18L
Permitted rim size	DW20B, W18L
Maximum air pressure [bar].	2,40
Section width (mm)	591
Outer diameter of tyre [mm].	1704
Stat. radius (SLR) [mm]	761
Rolling circumference [mm].	5109
Tread depth (mm)	58,0
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
163 A8	4875	40		2,40	
160 D	4500	65		2,40	