

TYRES

Product group	Tyres
Item number	15726856
Valid tyre size	IF 710 / 75 R 34 CFO
LI / SI / PR	184 A8 / 184 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.

Technical Informations

Item number	15726856
EAN	8903094058723
Valid tyre size	IF 710 / 75 R 34 CFO
LI / SI / PR	184 A8 / 184 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	351,50
Recommended rim size	25
Permitted rim size	23
Maximum air pressure [bar].	3,20
Section width (mm)	716
Tread width (mm)	676
Outer diameter of tyre [mm].	1930
Stat. radius (SLR) [mm]	870
Speed Radius Index (SRI)	900
Rolling circumference [mm].	5852
Tread depth (mm)	61,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	849
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 A8	9000	40		3,20	
184 B	9000	50		3,20	