

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 15726929 |
| Valid tyre size | 520 / 70 R 38 |
| LI / SI / PR | 150 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 765 |



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Low soil compaction and good self-cleaning properties.
- Mainly used both in arable farming and grassland.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 15726929 |
| EAN | 8903094062232 |
| Valid tyre size | 520 / 70 R 38 |
| LI / SI / PR | 150 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 765 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 166,01 |
| Recommended rim size | W16L |
| Permitted rim size | W15L, W18L |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 516 |
| Outer diameter of tyre [mm]. | 1749 |
| Stat. radius (SLR) [mm] | 793 |
| Rolling circumference [mm]. | 5300 |
| Tread depth (mm) | 53,5 |
| Number of lugs | 21x2 |
| Lug width (mm) | 43 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 150 D | 3350 | 65 | | 1,60 | |