

TYRES

Product group	Tyres
Item number	15726945
Valid tyre size	580 / 70 R 38
LI / SI / PR	180 A8 / 180 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Low soil compaction and good self-cleaning properties.
- Mainly used both in arable farming and grassland.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726945
EAN	8903094038510
Valid tyre size	580 / 70 R 38
LI / SI / PR	180 A8 / 180 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	239,55
Recommended rim size	W18L
Maximum air pressure [bar].	4,60
Section width (mm)	577
Outer diameter of tyre [mm].	1827
Stat. radius (SLR) [mm]	821
Rolling circumference [mm].	5505
Tread depth (mm)	58,0
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
180 A8	8000	40		4,60	
180 B	8000	50		4,60	