

TYRES

Product group	Tyres
Item number	15726951
Valid tyre size	710 / 70 R 38
LI / SI / PR	171 D / 168 E
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Sirio



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- New radial tyre for powerful tractors over 250 hp. Thanks to Speed Index E, this tyre allows high load capacities at speeds up to 70 km/h.
- The constant and uniform contact area reduces rolling resistance and fuel consumption
- Excellent ride comfort due to flexible sidewalls
- The special casing design with 6 polyester belts provides superb stability on the road and in the field
- A new sidewall compound and improved bead result in perfect heat dissipation

Technical Informations

Item number	15726951
EAN	8903094044283
Valid tyre size	710 / 70 R 38
LI / SI / PR	171 D / 168 E
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Sirio
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	306,00
Recommended rim size	DW23B
Permitted rim size	DW25B
Maximum air pressure [bar].	2,40
Section width (mm)	716
Tread width (mm)	650
Outer diameter of tyre [mm].	1959
Stat. radius (SLR) [mm]	887
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5840
Tread depth (mm)	62,0
Number of lugs	20x2
Lug width (mm)	55
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
171 D	6150	65		2,40	
168 E	5600	70		2,40	