

TYRES

Product group	Tyres	
Item number	15726957	
Valid tyre size	710 / 70 R 38	
LI / SI / PR	178 A8 / 175 D	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Agrimax RT 765	



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.



Technical Informations

Item number	15726957
EAN	8903094063499
Valid tyre size	710 / 70 R 38
LI / SI / PR	178 A8 / 175 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	230,23
Recommended rim size	DW23B
Maximum air pressure [bar].	3,20
Section width (mm)	716
Outer diameter of tyre [mm].	1959
Stat. radius (SLR) [mm]	859
Rolling circumference [mm].	5751
Tread depth (mm)	58,5
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 A8	7500	40		3,20	
175 D	6900	65		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.