

TYRES

Product group	Tyres
Item number	15726959
Valid tyre size	710 / 70 R 38
LI / SI / PR	178 A8 / 175 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765M





Notes and features

- The BKT Agrimax RT 765M is a 70 series radial tyre for tillage, field and transport use, grape harvesting and other applications.
- Its large contact area provides very good traction with low soil compaction.
- The tyre is characterised by very good self-cleaning properties.



Technical Informations

Item number	15726959
EAN	8903094066803
Valid tyre size	710 / 70 R 38
LI / SI / PR	178 A8 / 175 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765M
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	299,59
Recommended rim size	DW23B
Permitted rim size	DW25B
Maximum air pressure [bar].	3,20
Section width (mm)	716
Outer diameter of tyre [mm].	1959
Stat. radius (SLR) [mm]	859
Rolling circumference [mm].	5751
Tread depth (mm)	58,5
Number of lugs	20x2
Tyre capacity 75% [ltr.]	862.5
E-Ready	No



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 A8	7500	40		3,20	
175 D	6900	65		3,20	