

TYRES

| Product group | Tyres | |
|-----------------|-----------------|--|
| Item number | 15726961 | |
| Valid tyre size | 710 / 70 R 38 | |
| LI / SI / PR | 166 D | |
| TL/TT | TL | |
| Brand | BKT | |
| Tread pattern | Agrimax RT 765M | |





Notes and features

- The BKT Agrimax RT 765M is a 70 series radial tyre for tillage, field and transport use, grape harvesting and other applications.
- Its large contact area provides very good traction with low soil compaction.
- The tyre is characterised by very good self-cleaning properties.



Technical Informations

| Item number | 15726961 |
|------------------------------|-----------------|
| | |
| EAN | 8903094066773 |
| Valid tyre size | 710 / 70 R 38 |
| LI / SI / PR | 166 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 765M |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 284,48 |
| Recommended rim size | DW23B |
| Permitted rim size | DW25B |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 716 |
| Outer diameter of tyre [mm]. | 1959 |
| Stat. radius (SLR) [mm] | 859 |
| Speed Radius Index (SRI) | 925 |
| Rolling circumference [mm]. | 5751 |
| Tread depth (mm) | 58,5 |
| Number of lugs | 20x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 166 D | 5300 | 65 | | 1,60 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.