

TYRES

Product group	Tyres
Item number	15726973
Valid tyre size	620 / 70 R 42
LI / SI / PR	173 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726973
EAN	8903094063369
Valid tyre size	620 / 70 R 42
LI / SI / PR	173 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	237,50
Recommended rim size	DW20B
Permitted rim size	DW18L
Maximum air pressure [bar].	3,20
Section width (mm)	625
Outer diameter of tyre [mm].	1935
Stat. radius (SLR) [mm]	876
Rolling circumference [mm].	5804
Tread depth (mm)	57,5
Number of lugs	21x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 D	6500	65		3,20	