

TYRES

Product group	Tyres
Item number	15726977
Valid tyre size	710 / 70 R 42
LI / SI / PR	179 A8 / 176 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765M



Notes and features

 The BKT Agrimax RT 765M is a 70 series radial tyre for tillage, field and transport use, grape harvesting and other applications.

- Its large contact area provides very good traction with low soil compaction.
- The tyre is characterised by very good self-cleaning properties.



Technical Informations

Item number	15726977
EAN	8903094066469
Valid tyre size	710 / 70 R 42
LI / SI / PR	179 A8 / 176 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765M
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	326,28
Recommended rim size	DW23B
Maximum air pressure [bar].	2,80
Section width (mm)	716
Outer diameter of tyre [mm].	2061
Stat. radius (SLR) [mm]	922
Rolling circumference [mm].	6174
Tread depth (mm)	58,5
Number of lugs	21x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 A8	7750	40		2,80	
176 D	7100	65		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.