Bohnenkamp Moving Professionals

22.09.2024

TYRES

| Product group | Tyres | |
|-----------------|----------------------|--|
| Item number | 15726991 | |
| Valid tyre size | IF 750 / 75 R 46 CFO | |
| LI / SI / PR | 186 D | |
| TL/TT | TL | |
| Brand | ВКТ | |
| Tread pattern | Agrimax Force | |



Notes and features

- BKT Agrimax Force is an IF tyre for high performance tractors with more than 250 hp.
- It offers 20% higher load capacity at the same air pressure or the same load capacity at 20% lower air pressure compared to a standard tyre.
- The large contact area enables a uniform distribution of ground pressure and therefore optimum soil protection.
- Its strong polyester belt carcass provides good traction and stability on all surfaces and long tyre life.
- The tyre guarantees driving comfort in the field and during transport trips on the road without the need to adjust the air pressure.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 15726991 |
|------------------------------|----------------------|
| EAN | 8903094058082 |
| Valid tyre size | IF 750 / 75 R 46 CFO |
| LI / SI / PR | 186 D |
| TL/TT | TL |
| Brand | ВКТ |
| Tread pattern | Agrimax Force |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 482,36 |
| Recommended rim size | DW25B |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 742 |
| Tread width (mm) | 725 |
| Outer diameter of tyre [mm]. | 2294 |
| Stat. radius (SLR) [mm] | 1032 |
| Speed Radius Index (SRI) | 1075 |
| Rolling circumference [mm]. | 6802 |
| Contact area [cm²] | 4380 |
| Tread depth (mm) | 71,5 |
| Number of lugs | 23x2 |
| Tyre capacity 75% [ltr.] | 1113.75 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 186 D | 9500 | 65 | | 2,40 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.