

TYRES

Product group	Tyres
Item number	15727042
Valid tyre size	440 / 65 R 20
LI / SI / PR	141 A8 / 138 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax RT 657





Notes and features

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp.
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils.
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection.
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption.
- For road transport, the tyre is approved for speeds up to 65 km/h.



Technical Informations

Item number	15727042
EAN	8903094042753
Valid tyre size	440 / 65 R 20
LI / SI / PR	141 A8 / 138 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 657
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	68,00
Recommended rim size	W14L
Permitted rim size	W13, W15L
Maximum air pressure [bar].	2,40
Section width (mm)	441
Tread width (mm)	415
Outer diameter of tyre [mm].	1080
Stat. radius (SLR) [mm]	479
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3240
Tread depth (mm)	45,0
Number of lugs	19x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 A8	2575	40		2,40	
138 D	2360	65		2,40	