

TYRES

Product group	Tyres
Item number	15727044
Valid tyre size	420 / 65 R 20
LI / SI / PR	138 A8 / 135 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 657



Notes and features

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp.
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils.
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection.
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption.
- For road transport, the tyre is approved for speeds up to 65 km/h.

Technical Informations

Item number	15727044
EAN	8903094041862
Valid tyre size	420 / 65 R 20
LI / SI / PR	138 A8 / 135 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 657
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	61,08
Recommended rim size	W13
Permitted rim size	W11, W12
Maximum air pressure [bar].	2,40
Section width (mm)	418
Tread width (mm)	394
Outer diameter of tyre [mm].	1054
Stat. radius (SLR) [mm]	468
Speed Radius Index (SRI)	500
Rolling circumference [mm].	3162
Tread depth (mm)	38,0
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 A8	2360	40		2,40	
135 D	2180	65		2,40	