

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 15727045 |
| Valid tyre size | 440 / 65 R 24 |
| LI / SI / PR | 138 A8 / 135 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 657 |



Notes and features

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp.
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils.
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection.
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption.
- For road transport, the tyre is approved for speeds up to 65 km/h.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 15727045 |
| EAN | 8903094029136 |
| Valid tyre size | 440 / 65 R 24 |
| LI / SI / PR | 138 A8 / 135 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 657 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 79,75 |
| Recommended rim size | W14L |
| Permitted rim size | W13, W15L, DW13 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 441 |
| Tread width (mm) | 415 |
| Outer diameter of tyre [mm]. | 1182 |
| Stat. radius (SLR) [mm] | 538 |
| Speed Radius Index (SRI) | 575 |
| Rolling circumference [mm]. | 3546 |
| Tread depth (mm) | 44,5 |
| Number of lugs | 20x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 138 A8 | 2360 | 40 | | 2,40 | |
| 135 D | 2180 | 65 | | 2,40 | |