

TYRES

Product group	Tyres
Item number	15727050
Valid tyre size	480 / 65 R 24
LI / SI / PR	143 A8 / 140 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 657



Notes and features

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp.
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils.
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection.
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption.
- For road transport, the tyre is approved for speeds up to 65 km/h.

Technical Informations

Item number	15727050
EAN	8903094028528
Valid tyre size	480 / 65 R 24
LI / SI / PR	143 A8 / 140 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 657
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	93,08
Recommended rim size	W15L
Permitted rim size	W14L
Maximum air pressure [bar].	2,40
Section width (mm)	479
Tread width (mm)	454
Outer diameter of tyre [mm].	1234
Stat. radius (SLR) [mm]	562
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3730
Tread depth (mm)	47,0
Number of lugs	19x2
Lug width (mm)	3-4
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 A8	2725	40		2,40	
140 D	2500	65		2,40	