

## TYRES

|                 |                |
|-----------------|----------------|
| Product group   | Tyres          |
| Item number     | 15727085       |
| Valid tyre size | 440 / 65 R 28  |
| LI / SI / PR    | 141 A8 / 138 D |
| TL/TT           | TL             |
| Brand           | BKT            |
| Tread pattern   | Agrimax RT 657 |



## Notes and features

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp.
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils.
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection.
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption.
- For road transport, the tyre is approved for speeds up to 65 km/h.

**Technical Informations**

|                              |                |
|------------------------------|----------------|
| Item number                  | 15727085       |
| EAN                          | 8903094029143  |
| Valid tyre size              | 440 / 65 R 28  |
| LI / SI / PR                 | 141 A8 / 138 D |
| TL/TT                        | TL             |
| Brand                        | BKT            |
| Tread pattern                | Agrimax RT 657 |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 86,14          |
| Recommended rim size         | W14L           |
| Permitted rim size           | W13, W15L      |
| Maximum air pressure [bar].  | 2,40           |
| Section width (mm)           | 441            |
| Tread width (mm)             | 415            |
| Outer diameter of tyre [mm]. | 1283           |
| Stat. radius (SLR) [mm]      | 590            |
| Speed Radius Index (SRI)     | 625            |
| Rolling circumference [mm].  | 3927           |
| Tread depth (mm)             | 45,0           |
| Number of lugs               | 21x2           |
| Lug width (mm)               | 3              |
| E-Ready                      | No             |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 141 A8 | 2575               | 40           |               | 2,40                     |              |
| 138 D  | 2360               | 65           |               | 2,40                     |              |