

TYRES

Product group	Tyres
Item number	15727113
Valid tyre size	VF 520 / 60 R 28 NRO
LI / SI / PR	149 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax V-Flecto



Notes and features

- The BKT Agrimax V-Flecto is a VF tyre of the new generation.
- Compared with a standard tyre, the tyre achieves 40% more load capacity at the same inflation pressure or the same load capacity with 40% less inflation pressure.
- In contrast to most VF tyres, the tyre can be mounted on a standard rim (NRO=Narrow Rim Option).
- Its 10 % larger contact area compared with a standard tyre enables outstanding traction while significantly reducing soil compaction.
- The specially shaped bead (Bead Protection System) closes extremely airtight and keeps the inflation pressure constant in all conditions.
- During road journeys, the particular lug angles ensure reduced vibrations and noise levels.
- There is no need to adjust the inflation pressure for optimum performance both in the field and on the road
- The extremely strong polyester casing provides a 10 % longer service life in comparison with a standard tyre, even in difficult conditions.

Technical Informations

Item number	15727113
EAN	8903094060733
Valid tyre size	VF 520 / 60 R 28 NRO
LI / SI / PR	149 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax V-Flecto
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	121,44
Recommended rim size	DW18L
Permitted rim size	W18L
Maximum air pressure [bar].	1,60
Section width (mm)	516
Tread width (mm)	490
Outer diameter of tyre [mm].	1335
Stat. radius (SLR) [mm]	587
Speed Radius Index (SRI)	650
Rolling circumference [mm].	3910
Tread depth (mm)	47,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	254.22
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 D	3250	65		1,60	