

TYRES

Product group	Tyres
Item number	15727116
Valid tyre size	600 / 70 R 28
LI / SI / PR	157 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax RT 765



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.



Technical Informations

Item number	15727116
EAN	8903094067251
Valid tyre size	600 / 70 R 28
LI / SI / PR	157 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	170,00
Recommended rim size	DW18L
Permitted rim size	DW20B
Maximum air pressure [bar].	2,40
Section width (mm)	591
Outer diameter of tyre [mm].	1551
Stat. radius (SLR) [mm]	696
Rolling circumference [mm].	4692
Tread depth (mm)	57,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 D	4125	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.