Bohnenkamp Moving Professionals

21.09.2024

TYRES

Product group	Tyres	
Item number	15727124	
Valid tyre size	IF 710 / 60 R 30 CFO	
LI / SI / PR	168 D	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Agrimax Force	



Notes and features

- BKT Agrimax Force is an IF tyre for high performance tractors with more than 250 hp.
- It offers 20% higher load capacity at the same air pressure or the same load capacity at 20% lower air pressure compared to a standard tyre.
- The large contact area enables a uniform distribution of ground pressure and therefore optimum soil protection.
- Its strong polyester belt carcass provides good traction and stability on all surfaces and long tyre life.
- The tyre guarantees driving comfort in the field and during transport trips on the road without the need to adjust the air pressure.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number 15727124 EAN 8903094038541 Valid tyre size IF 710 / 60 R 30 CFO LI / SI / PR 168 D	
Valid tyre size IF 710 / 60 R 30 CFO	
LI / SI / PR 168 D	
TL/TT TL	
Brand BKT	
Tread pattern Agrimax Force	
Antistatic No	
Tyre colour Black	
ECE regulation number ECE 106	
Nettogewicht [kg] (gültig) 220,60	
Recommended rim size DW25B	
Maximum air pressure [bar]. 2,40	
Section width (mm) 708	
Tread width (mm) 665	
Outer diameter of tyre [mm]. 1614	
Stat. radius (SLR) [mm] 714	
Speed Radius Index (SRI) 775	
Rolling circumference [mm]. 4814	
Tread depth (mm) 58,5	
Number of lugs 18x2	
E-Ready No	

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 D	5600	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.