

## TYRES

Product group	Tyres
Item number	15727125
Valid tyre size	800 / 65 R 32 CHO
LI / SI / PR	178 A8 / 175 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris



## Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.

## Technical Informations

Item number	15727125
EAN	8903094031412
Valid tyre size	800 / 65 R 32 CHO
Alternative size 1	30.5LR32
LI / SI / PR	178 A8 / 175 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	327,66
Recommended rim size	DW27B
Permitted rim size	DW25B, DH27B
Maximum air pressure [bar].	3,20
Section width (mm)	818
Tread width (mm)	735
Outer diameter of tyre [mm].	1853
Stat. radius (SLR) [mm]	838
Rolling circumference [mm].	5587
Tread depth (mm)	57,0
Number of lugs	20x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 A8	7500	40		3,20	
175 B	6900	50		3,20	