

TYRES

| | |
|-----------------|-------------------|
| Product group | Tyres |
| Item number | 15727125 |
| Valid tyre size | 800 / 65 R 32 CHO |
| LI / SI / PR | 178 A8 / 175 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax Teris |



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.

Technical Informations

| | |
|------------------------------|-------------------|
| Item number | 15727125 |
| EAN | 8903094031412 |
| Valid tyre size | 800 / 65 R 32 CHO |
| Alternative size 1 | 30.5LR32 |
| LI / SI / PR | 178 A8 / 175 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax Teris |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 327,66 |
| Recommended rim size | DW27B |
| Permitted rim size | DW25B, DH27B |
| Maximum air pressure [bar]. | 3,20 |
| Section width (mm) | 818 |
| Tread width (mm) | 735 |
| Outer diameter of tyre [mm]. | 1853 |
| Stat. radius (SLR) [mm] | 838 |
| Rolling circumference [mm]. | 5587 |
| Tread depth (mm) | 57,0 |
| Number of lugs | 20x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 178 A8 | 7500 | 40 | | 3,20 | |
| 175 B | 6900 | 50 | | 3,20 | |