

## **TYRES**

Product group	Tyres	
Item number	15727128	
Valid tyre size	900 / 60 R 32 CHO	
LI / SI / PR	185 A8 / 182 B	
TL/TT	TL	
Brand	BKT	
Tread pattern	Agrimax Teris	



## Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.



## **Technical Informations**

Item number	15727128
EAN	8903094040865
Valid tyre size	900 / 60 R 32 CHO
LI / SI / PR	185 A8 / 182 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	406,00
Recommended rim size	DW27B
Permitted rim size	DW28B, DW30B
Maximum air pressure [bar].	4,00
Section width (mm)	886
Tread width (mm)	835
Outer diameter of tyre [mm].	1910
Stat. radius (SLR) [mm]	875
Speed Radius Index (SRI)	900
Rolling circumference [mm].	5775
Tread depth (mm)	58,5
Number of lugs	18x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
185 A8	9250	40		4,00	
182 B	8500	50		4,00	