

## TYRES

Product group	Tyres
Item number	15727129
Valid tyre size	540 / 65 R 34
LI / SI / PR	152 D / 149 E
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Sirio



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- New radial tyre for powerful tractors over 250 hp. Thanks to Speed Index E, this tyre allows high load capacities at speeds up to 70 km/h.
- The constant and uniform contact area reduces rolling resistance and fuel consumption
- Excellent ride comfort due to flexible sidewalls
- The special casing design with 6 polyester belts provides superb stability on the road and in the field
- A new sidewall compound and improved bead result in perfect heat dissipation

**Technical Informations**

Item number	15727129
EAN	8903094045297
Valid tyre size	540 / 65 R 34
LI / SI / PR	152 D / 149 E
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Sirio
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	157,53
Recommended rim size	W16L
Permitted rim size	W18
Maximum air pressure [bar].	2,40
Section width (mm)	530
Tread width (mm)	510
Outer diameter of tyre [mm].	1566
Stat. radius (SLR) [mm]	721
Speed Radius Index (SRI)	750
Rolling circumference [mm].	4735
Tread depth (mm)	50,0
Number of lugs	21x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 D	3550	65		2,40	
149 E	3250	70		2,40	