

TYRES

| Product group | Tyres |
|-----------------|----------------|
| Item number | 15727130 |
| Valid tyre size | 540 / 65 R 34 |
| LI / SI / PR | 155 A8 / 152 D |
| TL/TT | TL |
| Brand | ВКТ |
| Tread pattern | Agrimax RT 657 |





Notes and features

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp.
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils.
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection.
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption.
- For road transport, the tyre is approved for speeds up to 65 km/h.



Technical Informations

| Item number | 15727130 |
|------------------------------|----------------|
| EAN | 8903094028412 |
| Valid tyre size | 540 / 65 R 34 |
| LI / SI / PR | 155 A8 / 152 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 657 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 144,35 |
| Recommended rim size | W16L |
| Permitted rim size | W18L |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 530 |
| Tread width (mm) | 510 |
| Outer diameter of tyre [mm]. | 1566 |
| Stat. radius (SLR) [mm] | 712 |
| Speed Radius Index (SRI) | 750 |
| Rolling circumference [mm]. | 4742 |
| Tread depth (mm) | 50,0 |
| Number of lugs | 21x2 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 155 A8 | 3875 | 40 | | 2,40 | |
| 152 D | 3550 | 65 | | 2,40 | |