

## TYRES

|                 |                  |
|-----------------|------------------|
| Product group   | Tyres            |
| Item number     | 15727170         |
| Valid tyre size | IF 380 / 80 R 38 |
| LI / SI / PR    | 149 D            |
| TL/TT           | TL               |
| Brand           | BKT              |
| Tread pattern   | Agrimax Force    |



## Notes and features

- BKT Agrimax Force is an IF tyre for high performance tractors with more than 250 hp.
- It offers 20% higher load capacity at the same air pressure or the same load capacity at 20% lower air pressure compared to a standard tyre.
- The large contact area enables a uniform distribution of ground pressure and therefore optimum soil protection.
- Its strong polyester belt carcass provides good traction and stability on all surfaces and long tyre life.
- The tyre guarantees driving comfort in the field and during transport trips on the road without the need to adjust the air pressure.

## Technical Informations

|                              |                  |
|------------------------------|------------------|
| Item number                  | 15727170         |
| EAN                          | 8903094062140    |
| Valid tyre size              | IF 380 / 80 R 38 |
| LI / SI / PR                 | 149 D            |
| TL/TT                        | TL               |
| Brand                        | BKT              |
| Tread pattern                | Agrimax Force    |
| Antistatic                   | No               |
| Tyre colour                  | Black            |
| ECE regulation number        | ECE 106          |
| Nettogewicht [kg] (gültig)   | 111,14           |
| Recommended rim size         | W12              |
| Permitted rim size           | W11, W13         |
| Maximum air pressure [bar].  | 2,40             |
| Section width (mm)           | 380              |
| Tread width (mm)             | 340              |
| Outer diameter of tyre [mm]. | 1573             |
| Stat. radius (SLR) [mm]      | 725              |
| Speed Radius Index (SRI)     | 750              |
| Rolling circumference [mm].  | 4793             |
| Tread depth (mm)             | 44,5             |
| Number of lugs               | 26x2             |
| E-Ready                      | No               |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 149 D | 3250               | 65           |               | 2,40                     |              |