

TYRES

Product group	Tyres
Item number	15727190
Valid tyre size	650 / 65 R 38
LI / SI / PR	166 A8 / 163 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 657



Notes and features

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp.
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils.
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection.
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption.
- For road transport, the tyre is approved for speeds up to 65 km/h.

Technical Informations

Item number	15727190
EAN	8903094021383
Valid tyre size	650 / 65 R 38
LI / SI / PR	166 A8 / 163 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 657
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	226,44
Recommended rim size	DW20B
Permitted rim size	DW21B, DW23B
Maximum air pressure [bar].	2,40
Section width (mm)	645
Tread width (mm)	615
Outer diameter of tyre [mm].	1811
Stat. radius (SLR) [mm]	830
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5483
Tread depth (mm)	59,0
Number of lugs	20x2
Lug width (mm)	50
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 A8	5300	40		2,40	
163 D	4875	65		2,40	