

## TYRES

Product group	Tyres
Item number	15727192
Valid tyre size	650 / 65 R 38
LI / SI / PR	160 A8 / 157 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
- Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf.
- Large footprint enables excellent flotation properties.
- Reinforced bead provides high load capacity.

## Technical Informations

Item number	15727192
EAN	8903094053667
Valid tyre size	650 / 65 R 38
LI / SI / PR	160 A8 / 157 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	217,94
Recommended rim size	DW20B
Maximum air pressure [bar].	1,60
Section width (mm)	645
Tread width (mm)	590
Outer diameter of tyre [mm].	1811
Stat. radius (SLR) [mm]	833
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5443
Tread depth (mm)	59,0
Number of lugs	22x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		1,60	
157 D	4125	65		1,60	