

## **TYRES**

Product group	Tyres  15727195  IF 900 / 60 R 38 CFO  184 D  TL  BKT	
Item number		
Valid tyre size		
LI / SI / PR		
TL/TT		
Brand		
Tread pattern	Agrimax Force	





## Notes and features

- BKT Agrimax Force is an IF tyre for high performance tractors with more than 250 hp.
- It offers 20% higher load capacity at the same air pressure or the same load capacity at 20% lower air pressure compared to a standard tyre.
- The large contact area enables a uniform distribution of ground pressure and therefore optimum soil protection.
- Its strong polyester belt carcass provides good traction and stability on all surfaces and long tyre life.
- The tyre guarantees driving comfort in the field and during transport trips on the road without the need to adjust the air pressure.



## **Technical Informations**

Item number	15727195
EAN	8903094038749
Valid tyre size	IF 900 / 60 R 38 CFO
LI / SI / PR	184 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Force
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	431,50
Recommended rim size	DW30A
Permitted rim size	TW31B
Maximum air pressure [bar].	2,40
Section width (mm)	916
Tread width (mm)	840
Outer diameter of tyre [mm].	2045
Stat. radius (SLR) [mm]	904
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6107
Tread depth (mm)	61,5
Number of lugs	20x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 D	9000	65		2,40	