

## TYRES

Product group	Tyres
Item number	15727197
Valid tyre size	710 / 70 R 38
LI / SI / PR	181 A8 / 178 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
- Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf.
- Large footprint enables excellent flotation properties.
- Reinforced bead provides high load capacity.

## Technical Informations

Item number	15727197
EAN	8903094063420
Valid tyre size	710 / 70 R 38
LI / SI / PR	181 A8 / 178 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	261,77
Recommended rim size	DW23B
Permitted rim size	DW25B
Maximum air pressure [bar].	3,20
Section width (mm)	706
Tread width (mm)	630
Outer diameter of tyre [mm].	1959
Stat. radius (SLR) [mm]	881
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5926
Tread depth (mm)	48,0
Number of lugs	23x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 A8	8250	40		3,20	
178 D	7500	65		3,20	