

TYRES

Product group	Tyres	
Item number	15727300	
Valid tyre size	1050 / 50 R 32 CHO	
LI / SI / PR	184 A8 / 181 B	
TL/TT	TL	
Brand	BKT	
Tread pattern	Agrimax Teris	



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.



Technical Informations

Item number	15727300
EAN	8903094032723
Valid tyre size	1050 / 50 R 32 CHO
LI / SI / PR	184 A8 / 181 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	462,88
Recommended rim size	36.0VA
Maximum air pressure [bar].	3,20
Section width (mm)	1059
Tread width (mm)	980
Outer diameter of tyre [mm].	1893
Stat. radius (SLR) [mm]	840
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5685
Tread depth (mm)	60,0
Number of lugs	18x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 A8	9000	40		3,20	
181 B	8250	50		3,20	