

## TYRES

|                 |                |
|-----------------|----------------|
| Product group   | Tyres          |
| Item number     | 15727305       |
| Valid tyre size | 1050 / 50 R 32 |
| LI / SI / PR    | 184 A8 / 181 B |
| TL/TT           | TL             |
| Brand           | BKT            |
| Tread pattern   | Agrimax RT 600 |



## Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
- Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf.
- Large footprint enables excellent flotation properties.
- Reinforced bead provides high load capacity.

## Technical Informations

|                              |                |
|------------------------------|----------------|
| Item number                  | 15727305       |
| EAN                          | 8903094040728  |
| Valid tyre size              | 1050 / 50 R 32 |
| LI / SI / PR                 | 184 A8 / 181 B |
| TL/TT                        | TL             |
| Brand                        | BKT            |
| Tread pattern                | Agrimax RT 600 |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 426,06         |
| Recommended rim size         | 36.0VA         |
| Maximum air pressure [bar].  | 3,20           |
| Section width (mm)           | 1059           |
| Tread width (mm)             | 980            |
| Outer diameter of tyre [mm]. | 1863           |
| Stat. radius (SLR) [mm]      | 826            |
| Speed Radius Index (SRI)     | 875            |
| Rolling circumference [mm].  | 5700           |
| Tread depth (mm)             | 46,5           |
| Number of lugs               | 21x2           |
| E-Ready                      | No             |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 184 A8 | 9000               | 40           |               | 3,20                     |              |
| 181 B  | 8250               | 50           |               | 3,20                     |              |