

TYRES

Product group	Tyres
Item number	15727305
Valid tyre size	1050 / 50 R 32
LI / SI / PR	184 A8 / 181 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
- Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf.
- Large footprint enables excellent flotation properties.
- Reinforced bead provides high load capacity.

Technical Informations

Item number	15727305
EAN	8903094040728
Valid tyre size	1050 / 50 R 32
LI / SI / PR	184 A8 / 181 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	426,06
Recommended rim size	36.0VA mtlg.
Maximum air pressure [bar].	3,20
Section width (mm)	1059
Tread width (mm)	980
Outer diameter of tyre [mm].	1863
Stat. radius (SLR) [mm]	826
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5700
Tread depth (mm)	46,5
Number of lugs	21x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 A8	9000	40		3,20	
181 B	8250	50		3,20	