

TYRES

Product group	Tyres
Item number	15727435
Valid tyre size	210 / 95 R 32
LI / SI / PR	120 A8 / 120 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

Technical Informations

Item number	15727435
EAN	8903094040018
Valid tyre size	210 / 95 R 32
Alternative size 1	8.3R32
LI / SI / PR	120 A8 / 120 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	38,41
Recommended rim size	W7
Permitted rim size	W6
Maximum air pressure [bar].	3,20
Section width (mm)	214
Outer diameter of tyre [mm].	1213
Stat. radius (SLR) [mm]	571
Rolling circumference [mm].	3703
Tread depth (mm)	31,0
Number of lugs	28x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
120 A8	1400	40		3,20	
120 B	1400	50		3,20	