

TYRES

Product group	Tyres
Item number	15727445
Valid tyre size	230 / 95 R 32
LI / SI / PR	128 A8 / 128 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

Technical Informations

Item number	15727445
EAN	8903094026678
Valid tyre size	230 / 95 R 32
Alternative size 1	9.5R32
LI / SI / PR	128 A8 / 128 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	45,61
Recommended rim size	W8
Permitted rim size	W7
Maximum air pressure [bar].	4,00
Section width (mm)	238
Outer diameter of tyre [mm].	1251
Stat. radius (SLR) [mm]	585
Rolling circumference [mm].	3810
Tread depth (mm)	33,0
Number of lugs	27x2
Lug width (mm)	23
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 A8	1800	40		4,00	
128 B	1800	50		4,00	