

TYRES

Product group	Tyres
Item number	15727460
Valid tyre size	230 / 95 R 36
LI / SI / PR	130 A8 / 130 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

Technical Informations

Item number	15727460
EAN	8903094027477
Valid tyre size	230 / 95 R 36
Alternative size 1	9.5R36
LI / SI / PR	130 A8 / 130 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	48,50
Recommended rim size	W8
Permitted rim size	W7
Maximum air pressure [bar].	4,00
Section width (mm)	238
Outer diameter of tyre [mm].	1352
Stat. radius (SLR) [mm]	639
Rolling circumference [mm].	4112
Tread depth (mm)	33,0
Number of lugs	29x2
Lug width (mm)	23
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
130 A8	1900	40		4,00	
130 B	1900	50		4,00	