

TYRES

| Product group | Tyres | |
|-----------------|----------------|--|
| Item number | 15727460 | |
| Valid tyre size | 230 / 95 R 36 | |
| LI / SI / PR | 130 A8 / 130 B | |
| TL/TT | TL | |
| Brand | BKT | |
| Tread pattern | Agrimax RT 955 | |





Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h



Technical Informations

| Item number | 15727460 |
|------------------------------|----------------|
| EAN | 8903094027477 |
| Valid tyre size | 230 / 95 R 36 |
| Alternative size 1 | 9.5R36 |
| LI / SI / PR | 130 A8 / 130 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 955 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 48,50 |
| Recommended rim size | W8 |
| Permitted rim size | W7 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 238 |
| Outer diameter of tyre [mm]. | 1352 |
| Stat. radius (SLR) [mm] | 639 |
| Rolling circumference [mm]. | 4112 |
| Tread depth (mm) | 33,0 |
| Number of lugs | 29x2 |
| Lug width (mm) | 23 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 130 A8 | 1900 | 40 | | 4,00 | |
| 130 B | 1900 | 50 | | 4,00 | |